

MOBILE AUTOMATIC SLATTED COVER

2001a



FREEDOM MOBILITY AUTONOMY SAFETY






SPECIFICATIONS _

For pools from 2.5×3 m up to 5×12 m (including step).



- Single block frame available in several colours to harmonise the roller with the cover.
- 2 Tubular motorisation powered by high performance photovoltaic solar cells.
- Olymer blue, anti-marking wheels with a brake and a stop used to mark the roller's initial position.
- Lacquered aluminium central cross piece allowing water to drain into the pool.
- Cover composed of opaque PVC or polycarbonate solar slats fitted with locking kits.

Slats available in several colors for perfect matching with the Moove'O® roller.



Pushlock locking kit system Flexible stainless steel weight: in case you forgot to unlock the Pushlock when opening the cover, the material damage is reduced.



MOOVE'O IS A MOBILE AUTOMATIC SLATTED COVER THAT FREES THE AREA AROUND THE POOL. ITS EXCLUSIVE DESIGN MAKES IT POSSIBLE TO MOVE IT EFFORTLESSLY TO FULLY BENEFIT FROM THE SPACE 360° ALL-ROUND. AVAILABLE IN SEVERAL COLOURS, IT IS PERFECTLY ADAPTED TO YOUR ENVIRONMENT. ECONOMIC, IT RUNS ON SOLAR ENERGY.

AUTONOMY

Moove'O® is designed for new build or refurbished pools. Its mobility makes it possible to use it on wide angled, round cornered pools (polyester shell) or with cut corners (in-ground wood structures). It is equipped with a tubular motor powered using solar energy for rolling and unrolling the cover.

AESTHETIC

Its exclusive and discrete design makes Moove'O® the partner of the most aesthetically demanding projects. Its rail-less guiding system makes it possible for it to move along a straight trajectory, to keep the entire poolside area free. For perfect integration into the environment and the cover, Moove'O is available in 3 colors (white, beige, grey).


ECO-RESPONSIBLE

Covering your pool with a Moove'O® safety cover makes it possible to limit evaporation, responsible for drops in water levels, while maintaining the pool temperature and limiting external pollution. Its high power solar sensors stock the sun's energy in two batteries (rechargeable if necessary) and give it 100% economic performances.



Moove'O[®] lets you easily free up the space around your pool

In pool closure mode:



APPROACH MOOVE'O® TO THE POOL MANUALLY.



USE THE KEY OPERATED SWITCH TO AUTOMATICALLY Roll out the cover on the water.



RELEASE THE COVER AND PUSH MOOVE'O® BACK TO FREE UP THE POOL SIDE.



— FIJA Group —



MOBILE AUTOMATIC SLATTED COVER MOOVE

SLATS



Polycarbonate solar slats

Compliant with the NF P 90-308 standard (DEL exclusivity) Available in 6 colours: crystal black, crystal blue, crystal green, crystal, crystal brown and silver black* "Norm in process.



Opaque PVC slats

Compliant with the NF P 90-308 standard Available in 4 colours: grey, white, beige, blue



IVERNEA / IVERNEA PLUS

Remember to order your **winter shield Ivernea** or your **4 seasons protective covering Ivernea Plus** to protect the cover from UVs and dirt.



MAXIMUM SAFETY

An essential addition to DEL covers, the safety kits ensure the complete closure of your pool. A wide range of colours makes it possible to match the kits to your coating colour.



The purpose of DEL safety covers is not to replace the vigilance of parents and/or responsible adults which remains the essential factor for the safety of young children. DEL automatic covers are safety covers designed to prevent children under 5 years old from accessing the pool. A child can drown under in 3 minutes, no type of protective measure can replace the monitoring and vigilance of a responsible adult.

Please read carefully and keep in a safe place.

Moove'O[®] is a pool safety cover designed to prevent children under 5 years old from accessing the pool. This product complies with the NF P 90-308 standard. It is not a substitute for common sense or personal responsibility. The purpose of this cover is not to replace the vigilance of parents and/ or responsible adults which remains the essential factor for the safety of young children. A child can drown in under 3 minutes, no type of protective measure can replace the monitoring and vigilance of a responsible adult. **Guarantee:** 3 years for the moot and slats, 2 years for roller in compliance with our general sales terms and conditions. **Order form:** for the cover to be correctly fitted to the pool it is essential to supply a drawing of the pool with measurements taken every metre. In compliance with standard NF P 90-308, the gap between the inside of the pool and the edge of the cover must be less than 70 mm. **Manoeuvre time:** 3 minutes for automatic opening or closure plus 30 seconds to look or unlock the safety locking system. Moove'O[®] can be opened and closed by a single person. **Use:** in all seasons. For the cover to operate correctly maintain a constant water level corresponding to normal pool filtering. It is essential to fit a water level regulator. The water level must be compliant with the instructions. **Use limitations:** the installation of an automatic DEL cover on overflow pools and/or pools with steps on the length side (removable steps on the side) is not compliant with standard NF 90-308. In this case please use other compliant equipment. Unless otherwise specified by the manufacturer, immersion alarms are not compatible with DEL automatic covers. **Wintering:** close the pool for winter depending on the geographic location. Without lowering the water level, close the cover. If the water level is dropped to put the parts to insert above the water line, roll

the cover and secure the pool using a safety wintering cover. **Packing list:** for 5 x 10 m pool. Tube: 5 packs of 5.10 x 0.25 x 0.20 m, Moove'0[®] + locking kits: 1 pack of 5.7 x 0.80 x 0.70 m. Weight: 313 kg

Manufacturer: DEL La Basse Croix Rouge 35530 BRECE - France / export@fija-group.com / www.del-piscine.fr.

For more information about these products ask your pool professional for advice.

Distributor's stamp

